

**AUTOMATIC LAMINATOR**

Encapsulation both side lamination

distributed with **ALCHEMY**  
Trimming with or without margin.



Model AL-MEISTER ALM3220

Laminating Speed 500mm-1200mm/min. (Adjustable at every 100mm)

Temperature Range 80-130 °C

Warm-Up Time Approx. 5min.

Max. Laminating Thickness 0.4mm (400mic.)

Film Thicknesses 38-125mic. Exclusive Roll Film

Thickness of Objects 0.07-0.25mm (70-250mic. 65-240g/m<sup>2</sup>)

Paper Feeding Capacity: 200 sheets, Skew-Free Feature, Paper Guide

Applicable Sizes\*1 A3 with margin:without margin

A4 With margin:without margin

Trimming Methods 2 modes: with/without margin self determination system, Film Waste Box

Operation Panel LCD Monitor: Temperature setting, Speed setting, Current/Total counter,

Error messages, Margin setting

Operation button: Start, Stop, Up and Down, Setting, Temperature/Speed Switch

Indication Lamp: Speed, Temperature, Heat, Error

Other Features Lamination Counter Film Tension Control, Operation Lever

Automatic Stop at Film End, Power saving mode (Standby), Emergency halt function

Power Consumption 900W

Power Supply AC 110V, 120V, 220-240V

Net Weight Laminator: 50kg Stand: 22kg

Dimensions 1295(W) x 560(D) x 1100(H)mm

Attachments User Guide, Stand (Film Waste Box included)